

SCHEDULE OF QUANTITIES

SHEATHING
24 GAUGE FLAT GALV. IRON

NUMBER	TIMBER SIZE	LENGTH	DESCRIPTION	MARK	INSTRUCTIONS	QUANTITY
1	6" x 6"	8' 6"	6/1" 5" PILES	P	CUT ON SITE	22.5
2	3" x 3"	7' 8"	OUTSIDE SLEEPER PLATES	Z	PRECUT	11.5
5	4" x 2"	6' 8"	FLOOR JOISTS	J	"	22.1
4	4" x 1"	7' 8"	COVER BOARD AT SIDES	C1	"	10.1
4	4" x 1"	6' 10"	" " " END	C2	"	3.1
2	3" x 1"	7' 2"	BOTTOM WALL JOISTS AT SIDES W1	"	"	3.6
1	3" x 1"	6' 0"	" " " " END	W2	"	1.66
2	3" x 1"	2' 4"	" " " " "	W3	"	1.17
2	3" x 2"	7' 8"	TOP " " " SIDES T1	"	" NAIL JOINTS AT END	7.7
1	3" x 2"	6' 8"	TOP " " " END T2	"	" " " " "	3.33
1	3" x 2"	4' 5"	" " " " "	T3	"	2.3
1	3" x 2"	2' 0"	BELOW WINDOW OPENING	D	PRECUT	1.00
1	3" x 2"	2' 0"	LINTEL OVER DOOR	L	"	1.00
2	3" x 1"	5' 0"	WALL BRACING	V	CUT ON SITE, CHECKED W/JO PLANT & NAILED TO INTERIOR PART OF STUD	2.5
10	2" x 2"	3' 0"	STUDS	S1	PRECUT	10.0
2	3" x 2"	8' 0"	WINDOW STUDS	S2	"	3.0
2	3" x 2"	4' 7"	DOOR STUDS	S3	CUT & CHECK ON SITE	4.86
1	5" x 2"	2' 8"	2/1" 4" END WALL JACK STUDS	S4	" " " " "	1.33
15	3" x 1"	2' 0"	CRESTS	R1	CUT ON SITE	2.5
10	2" x 2"	3' 10"	RABBETS	R2	PRECUT & SHAPE FROM A TEMPLATE	12.8
2	2" x 2"	7' 0"	4/1" 3", 4/1" 8" PURLINS	R3	CUT ON SITE	4.66
1	4" x 1"	7' 8"	RIDGE BOARD	R4	PRECUT	2.5
2	4" x 2"	4' 4"	4/1" 8", 4/6" FLOOR TRAP TRIMMERS	X	CUT ON SITE	5.77
52.34 FT	6" x 1"	8' 0"	F & G FLOORING	Y	PRECUT	52.00

NUMBER	SIZE	POSITION	MARK	INSTRUCTIONS
3	8' 0" x 3' 0"	ROOF	G1	STANDARD SHEET
2	8' 0" x 4' 0"	SIDE WALLS	G2	"
4	5' 0" x 3' 0"	END WALLS	G3	CUT TO SHAPE ON SITE
1	2' 6" x 1' 0"	GABLE OVER DOOR	G4	"
1	2' 6" x 6"	BELOW DOOR	G5	PRECUT
1	2' 6" x 2' 0"	GABLE OVER WINDOW	"	CUT TO SHAPE ON SITE
1	2' 6" x 1' 6"	BELOW WINDOW	"	PRECUT

AREA OF SHEATHING 2051411 @ 18 1/2 OZS PER SQ FT = 242 LBS
 APPROX. TOTAL WEIGHT OF MATERIALS 856 LBS

SPECIFICATION

TIMBER - TIMBER TO BE AT SPECIFIED BRND OR EQUIVALENT. FLOORING, 1ST & 2ND GRADE TREATED RADIATA PINE. SUB-FLOOR TIMBER PRESSURE TREATED #1. FRAMING GRADE RADIATA PINE. FRAMING TIMBER TREATED #1A. FRAMING GRADE RADIATA PINE. ALL TIMBER TO BE WELL SEASONED.

AIR DROPPING - ALL MATERIALS TO BE PARACHUTED TO SITE.

SHEATHING - THE OUTSIDE OF WALL & ROOF FRAMING TO BE COVERED WITH 60/60 GRADE "SILKRAFT" TACKED IN PLACE. FLAT IRON SHEET TO BE PAINTED ON THE INSIDE AND UNDER LAPTS WITH "CARBOLETTIC" JUST BEFORE PLACING IN POSITION TO ENABLE "SILKRAFT" TO ADHERE TO SAME. SHEATHING TO BE FIXED WITH GALV. CLOUTS. SHEATHING TO BE FIXED WITH CLOUTS AT 6" C/LT ALONG ALL LAPTS, BRANTS AND PURLINS. OUTSIDE OF SHEATHING TO BE PRIMED AND PAINTED TENGRAINS. EACH HUT WILL BE ALLOCATED A NUMBER TO BE PAINTED ON ONE SIDE OF ROOF WITH BLACK PAINT. FIGURES TO BE 3' 0" HIGH WITH STROKES 4" WIDE.

GUY WIRES THESE MAY BE OMITTED WHEN HUT IS BUILT ON A SHELTERED SITE

ALLOWING 35% MA CUB FT - WEIGHT OF TIMBER = 530 LBS 2014825

MISCELLANEOUS

- 60 LIN FT 60/60 GRADE "SILKRAFT" 3' 0" WIDE
- 1 QUART CARBOLETTIC FOR PAINTING INSIDE OF SHEATHING & LAPTS
- 1 QUART TIN PRIMER FOR PAINTING OUTSIDE OF SHEATHING
- 1 QUART TIN TENGRAINE PAINT FOR PAINTING OUTSIDE OF SHEATHING
- 1 LB 1 1/4" x 1/2" GALV CLOUTS FOR FIXING SHEATHING
- 1 PKT TACKS TO HOLD "SILKRAFT" IN PLACE WHILE FIXING SHEATHING
- 3161 - 4" NAILS FOR FRAMING (ROOFHEADS)
- 118 - 2 1/2" NAILS FOR FRAMING (ROOFHEADS)
- 3161 - 3" NAILS FOR FRAMING (ROOFHEADS)
- 118 - 2" FLOOR BRDS

WEIGHT APPROX 24 LBS



B55

SHEET 4 OF 4 SHEETS

MARK	23/51	BIVOAC FOR D.P.F. 6' 0" x 7' 8"	5	86
DATE		SCHEDULE OF QUANTITIES & SPECIFICATION		
N.Z.		FOREST SERVICE, WELLINGTON		